

ROGUE EM 180



Inverter-based MIG welding system designed to address all your welding project needs.

- **Large Segment Display**
For clearing viewing
- **Synergic Weld Programs**
Full range of parameters
- **Arc Dynamics**
For MIG / MMA

Ordering Information

Description	Part Number
Rogue EM 180 Welding System	0700301091
Delivery includes: 180A MIG/MAG power source with mains cable 16 A plug 3 m, MXL 201 MIG Torch Euro 3 m, Return cable kit, OKC 35-50 16 mm ² , 3 m, Electrode holder Handy 200A heavy duty 50 mm OKC 3 m, Gas Hose with quick connect/open 4.5 m, ESAB OK AristoRod 12.50 0.8 mm 1 kg, ESAB GoldRox Electrode, 2.5 x 350 mm, 1 kg. Feed rolls 0.6/0.8 mm V (fitted), 0.8/0.9 mm V and 0.8/0.9 mm VK, Safety instruction.	

Specification

Mains Voltage	230 VAC ± 10%, 1ph, 50/60 Hz
Energy Save Mode	20 W
MIG (GMAW) Welding Output	180 A / 23.0 V at 25% 116 A / 19.8 V at 60% 90 A / 18.5 V at 100%
MMA (SMAW) Welding Output	150 A / 26.0 V at 25% 97 A / 23.9 V at 60% 75 A / 23.0 V at 100%
Current Range	30 – 180 A
Voltage Range	12 – 26 V
Wire Dimensions	
Mild Steel & Stainless Steel	0.6 – 1.0 mm
Cored Wire & Aluminium	0.8 – 1.0 mm
Wire Feed Speed	2.0 – 16.5 m/min
Max Spool Diameter	100 mm, 200 mm
Open Circuit Voltage	78 VDC
Efficiency at Max Current	82.70%
Power Factor at Max Current	0.8
Operating Temperature	-10 to +40°C
Protection Class	IP23S
Certification Mark (Standards)	CE
Dimensions L x W x H, incl. top handle	590 x 220 x 385 mm
Weight	16.2 kg

Options & Accessories

Description	Part Number
Trolley Rogue Mig	0460330882
MXL 201 Gas-cooled Torch with Euro Connection, 3 m	0700025220
MXL 201 Gas-cooled Torch with Euro Connection, 4 m	0700025221
Gas Hose, quick connect/open, 4.5 m	0349312105
Return cable kit, OKC 50, 3 m	0700006901
Electrode holder, Handy 200A, heavy duty 50 mm OKC, 3 m	0700006900
MMA 4 Analogue Remote Control incl. 10 m (33 ft) cable and 8-pin connector	0700500084
Bracket, Mounting, Trolley-CM3/Rogue	0447996231

Wear & Spare Parts

Feed Roll, 0.6/0.8 mm V	0367556001
Feed Roll, 0.8/1.0 mm V	0367556002
Feed Roll, 1.0/1.2 mm V	0367556003
Feed Roll, 0.9/1.2 mm VK	0349312497
Feed Roll, 1.0/1.2 mm U	0367556004
Guide, Inlet, Wire	0558102928
Guide, Outlet, Wire	0558102929
Key, Shaft, Motor, Drive	0558102930

Wear & Spare Parts

MXL 201 MIG Torch	
Contact Tip M6 x 25, 0.6 mm	0700200063
Contact Tip M6 x 25, 0.8 mm	0700200064
Contact Tip M6 x 25, 0.9 mm	0700200065
Contact Tip M6 x 25, 1.0 mm	0700200066
Gas Nozzle, Conical, ø 12 mm	0700200054
Gas Nozzle, Tapered, ø 9.5 mm	0700200060
Gas Nozzle, Cylindrical, ø 16 mm	0700200057
Gas Nozzle, FCAW, ø 6.5 mm	0700200105
Nozzle Spring	0700200078
Conduit/Liner, MXL, steel	0700200085
Conduit/Liner, MXL, aluminum	0700200091
Conduit/Liner, MXL, stainless steel	0700025816